



## Low flow comfort aerators

Best stream performance  
at lowest flow rates



flow, stop and go®

# 10M - the comfort improving alternative to SPRAY streams

For years, **spray streams** have been the well established and commonly used stream pattern for faucets with low flow rates of  $\leq 0.5$  gpm (as specified in commercial and public installations)



Today 10M is the **comfort improving alternative** for low flow rates with  $\leq 0.5$  gpm:

- soft & full aerated stream
- comfortable flow hardness & high rinsing power
- no splashing



## Best stream performance at minimum flow rates

- + Any aerator size feasible
- + Soft and full stream at low flow rates  $\leq 0.5$  gpm (1.9 l/min)
- + No splashing
- + Comfortable flow hardness with high rinsing power
- + Applicable for commercial faucets or wherever water saving is needed
- + Available flow classes: PCA 0.35 gpm max. and 0.5 gpm max.

# Adapter concept 10M

Logistics by Neoperl



Final customer product



PERLATOR TT  
PCA 0.35 or 0.5 gpm  
max.

Adapter STD size

PERLATOR HC  
STD 10M 0.5 gpm  
max.



# Any aerator size feasible (0.35/0.5 gpm max.)

TT  
size

TJ  
size

JR  
size

STD  
size

Cache



CACHE®  
TT 10M



CACHE® HC  
TJ 10M



CACHE® HC  
JR 10M



CACHE® HC  
STD 10M

Insert



PERLATOR® HC  
TT 10M



PERLATOR® HC  
TJ 10M



PERLATOR® HC  
JR 10M



PERLATOR® HC  
STD 10M

SLIM  
Air



SLIM Air JR US  
10M



SLIM Air  
STD 10M



**NEOPERL®**

flow, stop and go®